



...connecting to the aftermarket

Connects2Vision

User Manual

CAM-IV1

Iveco Reverse Camera
Iveco Daily 2011 - 2014

PRODUCT FEATURES:

Image Sensor: 1/4" CCD
TV Lines: 580
Current Consumption: 70-118mA @ 13.8V
Operating Voltage: 12V DC (Negative Ground)
Infra-Red LED's: Yes
Image: Mirror
Viewing Angle: 150 Degrees

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support centre: support.connects2.com

- Camera with 75cm cable to Male 4pin camera connector
- 10m 4pin to 4pin extension cable
- Camera connection cable with Female 4pin camera connector, 2x RCA Female connectors and Female DC connector
- 1.45 DC power cable with Male DC connector
- Male to Male RCA splice
- Instructions

INSTALLATION

1. Remove the third brake light housing from the vehicle and remove the brake light assembly.
2. Attach the brake light assembly to the CAM-IV1 and refit to the vehicle taking care not to trap any cables.
3. Connect the Black wire to a suitable ground and connect the Red wire to the reversing light circuit or an interface which provides a reverse signal.
4. Connect the camera to the 4pin extension cable, connect the extension cable to the camera connection cable and connect the camera connection cable to the display screen via the Yellow RCA connector and supplied RCA splice and ensure that the image is displayed correctly.



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2